



incl. VAT

NEW

Z1

ENDURO SERIES

Z-TURNS

Z1 107

Engine type	Cub Cadet
Engine displacement	679 cm ³
Rated power	11,6 kW / 2450 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	13,25 l
Lubrication	Full-pressure with spin-on oil filter
Transmission / Control	Dual Hydrostatic / Control lever / lap bar
Bag	optional
Grass deflector	Standard
Wheel size (f/r in inch)	11 x 6 / 20 x 10 - Turf Armor
Turning radius	0 cm
Lawn area (rec./up to)	10.000 m ² /h
Cutting width	107 cm
Cutting height (min.-max.)	25–114 mm
Cutting options	2-in-1
Deck engagement	Electric PTO
Deck height positions	15 positions
Wash nozzle / Mulch Kit	Standard / Standard
Mow in reverse	–
LpA / LwA / LwAg	85,6 / 98,8 / 100 dB (A)
Vibration value body / K-factor	0,4 / 0,2 m/s ²
Vibration value hand/arm / K-factor	2,1 / 1,1 m/s ²
Dimensions (L/W/H)	203 cm / 132 cm / 114 cm
Net weight	267 kg
Model number	17CAEACS603

SPECIAL FEATURES

New, modern design

Easy control via control lever

Solid steel tube frame construction

Comfortable, cushioned seat with backrest, adjustable

Robust, stamped cutting deck

POWERED BY
Cub Cadet



ZERO TURN





incl. VAT

NEW

Z1

ENDURO SERIES

Z-TURNS

Z1 107S

Engine type	Cub Cadet
Engine displacement	679 cm ³
Rated power	11,9 kW / 2500 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	13,25 l
Lubrication	Full-pressure with spin-on oil filter
Transmission / Control	Dual Hydrostatic / Dual foot pedal control
Bag	optional
Grass deflector	Standard
Wheel size (f/r in inch)	13 x 6,5 - Turfmaster / 20 x 8 - Multi Trac
Turning radius	0 cm
Lawn area (rec./up to)	10.000 m ² /h
Cutting width	107 cm
Cutting height (min.-max.)	25–114 mm
Cutting options	2-in-1
Deck engagement	Electric PTO
Deck height positions	15 positions
Wash nozzle / Mulch Kit	- / Standard
Mow in reverse	Standard
LpA / LwA / LwAg	86,1 / 98,9 / 100 dB (A)
Vibration value body / K-factor	0,3 / 0,2 m/s ²
Vibration value hand/arm / K-factor	2,0 / 1,0 m/s ²
Dimensions (L/W/H)	210 cm / 132 cm / 116 cm
Net weight	267 kg
Model number	17BAGBYE603

SPECIAL FEATURES

New, modern design

Synchro Steer technology: precise steering wheel control

Solid steel tube frame construction

Comfortable, cushioned seat with backrest, adjustable

Robust, stamped cutting deck

POWERED BY
Cub Cadet



ZERO TURN





incl. VAT

NEW

Z2

ENDURO SERIES

Z-TURNS

Z2 127

Powered by
Kawasaki

Engine type	Kawasaki FR691V
Engine displacement	726 cm ³
Rated power	14,5 kW / 2800 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	13,25 l
Lubrication	Full-pressure with spin-on oil filter
Transmission / Control	Dual Hydrostatic / Control lever / lap bar
Bag	optional
Grass deflector	Standard
Wheel size (f/r in inch)	11 x 6 / 20 x 10 - Turf Armor
Turning radius	0 cm
Lawn area (rec./up to)	11.500 m ² /h
Cutting width	127 cm
Cutting height (min.-max.)	25–114 mm
Cutting options	2-in-1
Deck engagement	Electric PTO
Deck height positions	15 positions
Wash nozzle / Mulch Kit	- / Standard
Mow in reverse	-
LpA / LwA / LwAg	89,8 / 102,6 / 105 dB (A)
Vibration value body / K-factor	0,6 / 0,3 m/s ²
Vibration value hand/arm / K-factor	4,0 / 2,0 m/s ²
Dimensions (L/W/H)	203 cm / 155 cm / 114 cm
Net weight	285 kg
Model number	17AIEAEL603



ZEROTURN

SPECIAL FEATURES

New, modern design

Easy control via control lever

Solid steel tube frame construction

Comfortable, cushioned seat with high backrest, adjustable

Robust, stamped cutting deck





incl. VAT

NEW

Z2

ENDURO SERIES

Z-TURNS

Z2 117S

Engine type	Kawasaki FR691V
Engine displacement	726 cm ³
Rated power	13,4 kW / 2450 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	13,25 l
Lubrication	Full-pressure with spin-on oil filter
Transmission / Control	Dual Hydrostatic / Dual foot pedal control
Bag	optional
Grass deflector	Standard
Wheel size (f/r in inch)	13 x 6,5 - Turf Armor / 20 x 8 - Turf Armor
Turning radius	0 cm
Lawn area (rec./up to)	10.500 m ² /h
Cutting width	117 cm
Cutting height (min.-max.)	25–114 mm
Cutting options	2-in-1
Deck engagement	Electric PTO
Deck height positions	15 positions
Wash nozzle / Mulch Kit	– / Standard
Mow in reverse	Standard
LpA / LwA / LwAg	85,4 / 98,9 / 100 dB (A)
Vibration value body / K-factor	0,3 / 0,2 m/s ²
Vibration value hand/arm / K-factor	3,0 / 1,5 m/s ²
Dimensions (L/W/H)	210 cm / 142 cm / 116 cm
Net weight	285 kg
Model number	17BIGBYN603

SPECIAL FEATURES

New, modern design

Synchro Steer technology: precise steering wheel control

Solid steel tube frame construction

Comfortable, cushioned seat with high backrest, adjustable

Robust, stamped cutting deck

Powered by
Kawasaki



ZEROTURN





incl. VAT

NEW

Z3

ENDURO SERIES

Z-TURNS

Z3 137

Engine type	Kawasaki FR691V
Engine displacement	726 cm ³
Rated power	14,7 kW / 2850 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	13,25 l
Lubrication	Full-pressure with spin-on oil filter
Transmission / Control	Dual Hydrostatic / Control lever / lap bar
Bag	optional
Grass deflector	Standard
Wheel size (f/r in inch)	11 x 6 / 20 x 12 - Turf Armor
Turning radius	0 cm
Lawn area (rec./up to)	12.500 m ² /h
Cutting width	137 cm
Cutting height (min.-max.)	25-114 mm
Cutting options	2-in-1
Deck engagement	Electric PTO
Deck height positions	15 positions
Wash nozzle / Mulch Kit	- / Standard
Mow in reverse	-
LpA / LwA / LwAg	90,2 / 102,8 / 105 dB (A)
Vibration value body / K-factor	0,5 / 0,3 m/s ²
Vibration value hand/arm / K-factor	3,9 / 2,0 m/s ²
Dimensions (L/W/H)	203 cm / 164 cm / 117 cm
Net weight	312 kg
Model number	17AIECE3603

Powered by
Kawasaki



ZERO TURN

SPECIAL FEATURES

New, modern design

Easy control via control lever

Solid steel tube frame construction

Comfortable, cushioned seat with high backrest, adjustable

Robust, stamped and specially reinforced cutting deck





incl. VAT

NEW

Z3

ENDURO SERIES

Z-TURNS

Z3 127S

Engine type	Kawasaki FR691V
Engine displacement	726 cm ³
Rated power	14,5 kW / 2800 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	13,25 l
Lubrication	Full-pressure with spin-on oil filter
Transmission / Control	Dual Hydrostatic / Dual foot pedal control
Bag	optional
Grass deflector	Standard
Wheel size (f/r in inch)	13 x 6,5 - Turf Armor / 20 x 12 - Turf Armor
Turning radius	0 cm
Lawn area (rec./up to)	11.500 m ² /h
Cutting width	127 cm
Cutting height (min.-max.)	25–114 mm
Cutting options	2-in-1
Deck engagement	Electric PTO
Deck height positions	15 positions
Wash nozzle / Mulch Kit	- / Standard
Mow in reverse	Standard
LpA / LwA / LwAg	89,8 / 102,6 / 105 dB (A)
Vibration value body / K-factor	0,6 / 0,3 m/s ²
Vibration value hand/arm / K-factor	4,0 / 2,0 m/s ²
Dimensions (L/W/H)	210 cm / 153 cm / 116 cm
Net weight	285 kg
Model number	17BIGGY2603

SPECIAL FEATURES

New, modern design

Synchro Steer technology: precise steering wheel control

Solid steel tube frame construction

Comfortable, cushioned seat with high backrest, adjustable

Robust, stamped and specially reinforced cutting deck

Powered by
Kawasaki



ZEROTURN



incl. VAT



XZ7 ENDURO SERIES®

Z-TURNS

XZ7 L122 - ULTIMA

Engine type	Kawasaki
Engine displacement	726 cm ³
Rated power	14,4 kW / 2700 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	20,8 l
Lubrication	Full-pressure with spin-on oil filter
Transmission / Control	Dual Hydrostatic / Control lever
Bag	optional (49A70001100)
Grass deflector	Standard
Wheel size (f/r in inch)	13 x 6,5 / 23 x 12
Turning radius	0 cm
Lawn area (rec./up to)	11.000 m ² /h
Cutting width	122 cm
Cutting height (min.-max.)	25–114 mm
Cutting options	3-in-1 option
Deck engagement	Electric PTO
Deck height positions	16 positions
Wash nozzle / Mulch Kit	– / Standard
Mow in reverse	Standard
LpA / LwA / LwAg	96,8 / 104,5 / 105 dB (A)
Vibration value body / K-factor	1,0 / 0,5 m/s ²
Vibration value hand/arm / K-factor	1,5 / 0,75 m/s ²
Dimensions (L/W/H)	232 cm / 145 cm / 134 cm
Net weight	415 kg
Model number	47AIAAA6603

SPECIAL FEATURES

Robust tubular steel frame and all-round reinforced mower deck

Premium seat with high backrest, padded armrests and special cushioning

Excellent grass collection

Spring-mounted front-wheel suspension

Foot controlled deck lift

3-in-1 OPTION

Powered by
Kawasaki



ZEROG TURN

**3 YEARS
500 HOURS***
WARRANTY
PRIVATE &
BUSINESS

incl. VAT



XZ7 ENDURO SERIES®

Z-TURNS

XZ7 L152i - ULTIMA

Engine type	KOHLER EFI
Engine displacement	747 cm ³
Rated power	14,8 kW / 2700 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	20,8 l
Lubrication	Full-pressure with spin-on oil filter
Transmission / Control	Dual Hydrostatic / Control lever
Bag	optional (49A70002100)
Grass deflector	Standard
Wheel size (f/r in inch)	13 x 6,5 / 24 x 12
Turning radius	0 cm
Lawn area (rec./up to)	15.000 m ² /h
Cutting width	152 cm
Cutting height (min.-max.)	25–114 mm
Cutting options	3-in-1 option
Deck engagement	Electric PTO
Deck height positions	16 positions
Wash nozzle / Mulch Kit	– / Standard
Mow in reverse	Standard
LpA / LwA / LwAg	97,2 / 104,7 / 105 dB (A)
Vibration value body / K-factor	1,0 / 0,5 m/s ²
Vibration value hand/arm / K-factor	2,0 / 1,0 m/s ²
Dimensions (L/W/H)	233 cm / 177 cm / 134 cm
Net weight	450 kg
Model number	47ATAHA8603

SPECIAL FEATURES

- Robust tubular steel frame and all-round reinforced mower deck
- Premium seat with high backrest, padded armrests and special cushioning
- Excellent grass collection
- Spring-mounted front-wheel suspension
- Foot controlled deck lift

3-in-1 OPTION

POWERED BY
KOHLER®



ZEROG TURN

**3 YEARS
500 HOURS***
WARRANTY
PRIVATE &
BUSINESS



incl. VAT

XZ8 ENDURO SERIES®

Z-TURNS

XZ8 S122 - ULTIMA

Engine type	Kawasaki
Engine displacement	726 cm ³
Rated power	14,4 kW / 2700 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	20,8 l
Lubrication	Full-pressure with spin-on oil filter
Transmission / Control	Dual Hydrostatic (Hydrogear ZT3100) / Dual foot pedal control
Bag	optional (49A70001100 + 490-950-C062)
Grass deflector	Standard
Wheel size (f/r in inch)	13 x 6,5 / 22 x 12
Turning radius	0 cm
Lawn area (rec./up to)	11.000 m ² /h
Cutting width	122 cm
Cutting height (min.-max.)	25–114 mm
Cutting options	3-in-1 option
Deck engagement	Electric PTO
Deck height positions	16 positions
Wash nozzle / Mulch Kit	– / Standard
Mow in reverse	Standard
LpA / LwA / LwAg	96,8 / 104,5 / 105 dB (A)
Vibration value body / K-factor	0,3 / 0,2 m/s ²
Vibration value hand/arm / K-factor	2,4 / 1,2 m/s ²
Dimensions (L/W/H)	218 cm / 138 cm / 121 cm
Net weight	436 kg
Model number	47AICAB6603

SPECIAL FEATURES

Good manoeuvrability and slope handling

Premium seat with high backrest and armrests, individually adjustable suspension

Robust tubular steel frame and fabricated mowing deck

Bright LED headlights

Foot controlled deck lift

3-in-1 OPTION

Powered by
Kawasaki



ZEROC TURN

**3 YEARS
500 HOURS***
WARRANTY
PRIVATE &
BUSINESS



incl. VAT

XZ8 ENDURO SERIES®

Z-TURNS

XZ8 S137i - ULTIMA

Engine type	KOHLER EFI
Engine displacement	747 cm ³
Rated power	13,8 kW / 2500 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	20,8 l
Lubrication	Full-pressure with spin-on oil filter
Transmission / Control	Dual Hydrostatic (Hydrogear ZT3200) / Dual foot pedal control
Bag	optional (49A70002100 + 490-950-C062)
Grass deflector	Standard
Wheel size (f/r in inch)	13 x 6,5 / 23 x 12
Turning radius	0 cm
Lawn area (rec./up to)	13.000 m ² /h
Cutting width	137 cm
Cutting height (min.-max.)	25–114 mm
Cutting options	3-in-1 option
Deck engagement	Electric PTO
Deck height positions	16 positions
Wash nozzle / Mulch Kit	– / Standard
Mow in reverse	Standard
LpA / LwA / LwAg	89,9 / 104,3 / 105 dB (A)
Vibration value body / K-factor	0,4 / 0,2 m/s ²
Vibration value hand/arm / K-factor	2,8 / 1,4 m/s ²
Dimensions (L/W/H)	218 cm / 153 cm / 121 cm
Net weight	449 kg
Model number	47ATCAB7603

SPECIAL FEATURES

Good manoeuvrability and slope handling

Premium seat with high backrest and armrests, individually adjustable suspension

Robust tubular steel frame and fabricated mowing deck

Bright LED headlights

Foot controlled deck lift

3-in-1 OPTION

POWERED BY
KOHLER



ZERO TURN





incl. VAT

Z-TURNS

Z5 152

Engine type	Kawasaki OHV
Engine displacement	852 cm ³
Rated power	15,8 kW / 2500 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	2 x 34 l
Lubrication	Pressure oil lubrication
Drive	Dual Hydrostatic
Transmission	Parker HTG 12 cc
Bag	Side discharge
Grass deflector	Standard
Wheel size (f/r in inch)	15 x 6 / 24 x 12
Turning radius	0 cm
Lawn area (rec./up to)	15.000 m ² /h
Cutting width	152 cm
Cutting height (min.-max.)	26–127 mm
Cutting options	2-in-1
Deck engagement	Electric PTO
Deck height positions	17 positions
Mulch Kit	Standard
Mow in reverse	Standard
LpA / LwA / LwAg	90,1 / 103,2 / 105 dB (A)
Vibration value body / K-factor	0,4 / 0,5 m/s ²
Vibration value hand/arm / K-factor	3,3 / 1,5 m/s ²
Dimensions (L/W/H)	230 cm / 160 cm / 134 cm
Net weight	680 kg
Model number	53BIHJUV603

Powered by
Kawasaki



ZERO
TURN

SPECIAL FEATURES

Amazing strength and outstanding comfort

Robust and strong mowing deck with 152 cm cutting width

Work efficiently and ride comfortably with PRO Z Air-Ride seat

Beefed-up front end





incl. VAT

Z-TURNS

Z9 183id

Engine type	Kawasaki FX1000V EFI
Engine displacement	999 cm ³
Rated power	19,3 kW / 2600 min ⁻¹
Cylinders	V-TWIN dual cylinder
Tank volume (capacity)	2 x 34 l, with fuel indicator l
Lubrication	Pressure oil lubrication
Drive	Dual Hydrostatic
Transmission	Parker HTG 16 cc
Bag	Side discharge
Grass deflector	Standard
Wheel size (f/r in inch)	16 x 6,5 / 24 x 12
Turning radius	0 cm
Lawn area (rec./up to)	18.000 m ² /h
Cutting width	183 cm
Cutting height (min.-max.)	26–127 mm
Cutting options	2-in-1
Deck engagement	Electric PTO
Deck height positions	17 positions
Mulch Kit	Standard
Mow in reverse	Standard
LpA / LwA / LwAg	87,3 / 102,5 / 105 dB (A)
Vibration value body / K-factor	0,7 / 0,35 m/s ²
Vibration value hand/arm / K-factor	2,6 / 1,3 m/s ²
Dimensions (L/W/H)	226 cm / 185 cm / 131 cm
Net weight	840 kg
Model number	53ALHMUY603

Powered by
Kawasaki



ZERO
TURN

SPECIAL FEATURES

High precision due to extremely wide duoble tires and all-wheel steering

Excellent climbing abilities on slopes with up to 25°

Power and economy combined

Electronically adjustable cutting deck

Work efficiently and ride comfortably with PRO Z Air-Ride seat

